Fukushima Daiichi Nuclear Power Station Plant Parameters

As of 11:00 on September 22 2021

[Note]

Some indicators might not be functioning properly beyond the normal condition for usage affected by the earthquake and subsequent events. We comprehensively evaluate situation in plants using all the available information from indicators and also focusing on trends, taking uncertainty of indicators into consideration.

	Unit 1	Unit 2	Unit 3	Unit 4
Status of water	FDW line: 2.0 m³/h	FDW line: 0.0 m³/h	FDW line: 2.6 m³/h	
injection to the	CS line: 1.4 m³/h	CS line: 2.6 m³/h	CS line: 0.0 m³/h %6	
reactor	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	
Temperature at the bottom of RPV	VESSEL BOTTOM HEAD			
	(TE-263-69L1) : 27.4 ℃	VESSEL WALL ABOVE BOTTOM HEAD	VESSEL BOTTOM ABOVE SKIRT JOT	
	VESSEL ABOVE SKIRT JOINT	(TE-2-3-69H3) : 33.0 °C	(TE-2-3-69F1): 31.4 °C	
	(TE-263-69H1): 26.7 °C	RPV TEMPERATURE	VESSEL WALL ABOVE BOTTOM HEAD	
	VESSEL DOWN COMMER	(TE-2-3-69R) : 33.0 ℃	(TE-2-3-69H1): 30.1 °C	
	(TE-263-69G2) : 26.8 °C	(as of 11:00, 9/22)	(as of 11:00, 9/22)	
	(as of 11:00, 9/22)			
Temperature in PCV	HVH-12A RETURN AIR	RETURN AIR DRYWELL COOLER	RETURN AIR DRYWELL COOLER	
	(TE-1625A) : 26.7 ℃	(TE-16-114B): 33.1 ℃	(TE-16-114A) : 32.0 ℃	
	HVH-12A SUPPLY AIR	SUPPLY AIR D/W COOLER HVH2-16B	SUPPLY AIR D/W COOLER	
	(TE-1625F) : 26.7 ℃	(TE-16-114G#1) : 32.9 ℃	(TE-16-114F#1) : 30.0 ℃	
	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	_
Pressure in PCV	0.21 kPag	4.23 kPag	0.42 kPa g	_
	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	
Flow rate of nitrogen gas injection to Reactors ※3	RPV (RVH-A) : - Nm³/h			
	(RVH-B): 15.22 Nm²/h	RPV-A: 6.44 Nm¹/h	RPV-A: 8.13 Nm³/h	
	(JP-A): 15.03 Nm³/h	RPV-B: 6.68 Nm ¹ /h	RPV-B: 8.64 Nm³/h	
	(JP-B): - Nm³/h	PCV: - Nm³/h **4	PCV: - Nm³/h **4	
	PCV: - Nm³/h **4	(as of 11:00, 9/22)	(as of 11:00, 9/22)	
Outlet flow from	(as of 11:00, 9/22)	40.70	1000	
PCV gas control	24.2 m³/h	16.73 Nm³/h	16.82 Nm³/h	
system	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	
Hydrogen concentration in PCV ※1	System A: 0.00 vol%	System A: 0.02 vol%	System A: 0.03 vol%	
		System B: 0.01 vol%	System B: 0.03 vol%	
	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	
Radioactive concentration in PCV (Xe 135) **2	System A:	System A:	System A:	
	indicated value 9.70E-04 Bq/cm³ detection limit 3.90E-04	indicated value ND Bg/cm³	indicated value ND Bg/cm³	
		detection limit 1.3E-01	detection limit 1.9E-01	
	System B:	System B:	System B:	
	indicated value 1.24E-03	indicated value ND Bg/cm³	indicated value ND Bg/cm³	
	actection with 3.232 34	detection limit 1.3E-01	detection limit 1.9E-01	
	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	
Temperature in the spent fuel	30.7 ℃	29.5 ℃	25.1 ℃	- ℃ ※5
lood	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)
FPC skimmer surge tank level	1.95 m	3.75 m	2.68 m	67.1 ×100mm
	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)	(as of 11:00, 9/22)

[Information about measurements]

^{*1:} In case that the instrument indicates minus hydrogen density, "0%" is recorded (Because there's the possibility of minus indication due to the instrumental precision when hydrogen density is very low.) The hydrogen concentration in the PCV gas control system is provided.

^{32:} In case that the instrument reading is below measurable limit. "ND" is recorded. The radioactivity density (Xe135) in the PCV gas control system is provided.

^{3:} Flow rate values are adjusted according to the temperature and the pressure under usage conditions.4: Nitrogen gas injection is under suspension.

^{3.5} The primary coolant pump in the Unit 4 spent fuel pool is now stopped operation

^{*6:} The reactor injection water flow rate is changed due to work in progress