Fukushima Daiichi Nuclear Power Station Plant Parameters

Some indicators might not be functioning properly beyond the normal condition for usage affected by the earthquake and subsequent events. We comprehensively evaluate situation in plants using all the available information from indicators and also focusing on trends, taking uncertainty

of indicators into consideration.

As of 1	2:00 on	February	26
---------	---------	----------	----

Water level in the reactor Water sexue in the reactor Pressure in the Syst Syst Syst	of 11:00, 2/26)	Unit 2 Fresh water feeding Feed water system 3.0 m²/h, CS line 5.9 m²/h (as of 11:00, 2/26) Fuel range A: Downscale	Unit 3 Fresh water feeding Feed water system 1.9 m³/h, CS line 5.0 m³/h (as of 11:00 , 2/26)	Unit 4		Unit 6	
Water level in the reactor Water level in the reactor Pressure in the Syst Syst	ed water system 4.4 n³/h, CS line 1.9 n³/h s of 11:00 , 2/26) el range A: Downscale el range B:-1660 mm	Feed water system 3.0 m²/h, CS line 5.9 m²/h (as of 11:00, 2/26) Fuel range A: Downscale #3	Feed water system 1.9 m³/h, CS line 5.0 m³/h			actor is functioning. Water	
Water level in the reactor Fuel (as constitution of the Pressure in the System System)	el range B:-1660 mm				%2 (Heat removal of the reactor is functioning, Water injection is unnecessary)		
Pressure in the Syst	stem A:-0.004 MPa g	(as of 11:00, 2/26)	Fuel range A:-1489 mm	3	Stoppage range 2509mm (as of 12:00, 2/26)	Stoppage range 1970mm (as of 12:00 , 2/26)	
las o	stem B:-MPa g	System A:0.014 MPa g System B:-MPa g (as of 11:00 , 2/26)) <u>*</u> 3) <u>*</u> 3	0.011 MPa g (as of 12:00 , 2/26)	0.021 MPa g (as of 12:00 , 2/26)	
Water temperature of the reactor	(Since there is no water inflow in the system it is impossible to collect the data)			35.9 °C (as of 12:00, 2/26)	25.8 °C (as of 12:00 , 2/26)		
Temperature around Tem	mperature in feed-water nozzle:24.0 °C mperature at reactor vessel bottom:24.2 °C of 11:00 , 2/26)	Temperature in feed-water nozzle:42.3 °C Temperature at reactor vessel bottom:44.7 °C (as of 11:00 , 2/26)	Temperature in feed-water nozzle:42.1 °C Temperature at reactor vessel bottom:52.6 °C (as of 11:00, 2/26)	%2 (Monitoring is	※2 (monitoring through wareactor)	ater temperature of the	
Pressure in D/W · S/C: (as c	C:0.118 MPa abs	D/W:0,118 MPa abs S/C: Downscale	D/W:0.1016 MPa abs S/C:0.1851 MPa abs (as of 11:00, 2/26)	unnecessary since all fuel are takeoff)			
D/W Atmosphere HVH	/H return:25.3 ℃	RPV bellow seal:56.5 ℃	RPV bellow seal:54.6 °C	3			
CAMS radiation S/C monitor	(B):4.91E+01Sv/h	D/W(A):6.33E+00Sv/h (B):2.52E+00Sv/h	D/W(A):2.88E+00Sv/h (B):1.84E+00Sv/h (S):2.30E-01Sv/h (B):2.20E-01Sv/h (as of 11:00 , 2/26)	3	※2 (Monitoring is unnecessary reactor is functioning.) **The content of the content of th	(Monitoring is unnecessary since heat removal of	
Temperature in S/C Syst	stem B:33.3 °C	System A:33.3 °C System B:33.1 °C (as of 11:00 , 2/26)	System A:28.7 °C System B:28.7 °C (as of 11:00 , 2/26)				
Hydrogen concentration in PCV	0.00vol% (as of 11:00 , 2/26)	0.07vol% (as of 11:00 , 2/26) **3	-				
pressure		0.384MPa g (0.485MPa abs)	0.384MPa g (0.485MPa abs)				
Designed usable D/W maximum pressure 0.42	127MPa g (0.528MPa abs)	0.427MPa g (0.528MPa abs)	0.427MPa g (0.528MPa abs)	_		_	
Temperature in the spent fuel pool	26.5°C (as of 11:00 , 2/26)	13.9°C (as of 11:00 , 2/26)	13.9°C (as of 11.00 , 2/26)	26℃ (as of 11:00 , 2/26)	18.0 °C (as of 12:00 , 2/26)	23.0 °C (as of 12:00 , 2/26)	
FPC skimmer surge tank level	3170mm (as of 11:00 , 2/26)	2890mm (as of 11:00 , 2/26)	4140mm (as of 11:00 , 2/26)	4770mm (as of 11:00, 2/26)	*	32	
Power source	Receiving offsite p	oower (P/C2C)	Receiving offsite power (P/C4	D)	Receiving o	ffsite power	
Others				Temperature in the Common Spent Fuel Storage: 18°C (as of 10:00 , 2/26	5u : SHC mode (from 14:28 ,2/15)	6u : SHC mode (from 11:17 ,2/23)	

Pressure conversion Gauge pressure (MPa g) = Absolute pressure (MPa abs) - atmospheric pressure (normal atmospheric pressure 0.1013 MPa)

Absolute pressure (MPa abs) = Gauge pressure (MPa g) + atmospheric pressure (normal atmospheric pressure 0.1013 MPa)

*1 : Instrument failure*2 : Not covered for colleting data

*3 : continuously monitoring the status

Fukushima Daiichi Nuclear Power Station Supplemental explanation for the plant parameters

■Supplemental explanation for each parameter

Item	Recording manner	Measurement manner	Ch number or number of systems
Status of water injection to the reactor	Water inflow (CS line: Core Spray system)	Temporary	System 1 / 1
Water level in the reactors	Data measured by the water gauge, which monitor the fuel range	Temporary	System A 1/1Ch System B 1/1Ch
Pressure in the reactor	One representing value is noted among multiple data on each System A, B. Readings of temporary instruments are represented in A system for Unit 1 and 2.	Temporary	1/1 system (Unit 1/2) System A 1/2Ch, System B 1/2Ch (Unit 3)
Temperature in the reactor	Since there is no water inflow at the points, where thermometers are set, no data is collected.	_	-
	Data measured at feed-water nozzle and at reactor vessel bottom (1U, 3U: RPV Bottom Head, 2U: RPV Wall Above Bottom Head) are noted among multiple data to view the whole picture.	Temporary	Point of Feed-water nozzle reactor vessel bottom 1/4Ch (Unit1) 1/1Ch (Unit2/3)
Pressure in D/W • S/C	Data from temporary instrument. (D/W: Dry Well、S/C: Suppression Chamber)	Temporary	(D/W) wide range 1 / 1Ch (Unit 1) 1 / 4Ch (Unit 2/3) (S/C) 1 / 1system (Unit 1/2) 1 / 2Ch (Unit 3)
	Data at upper point (RPV Bellows Air) and middle point (HVH return) are noted among multiple data to view the whole picture. (RPV : Reactor Pressure Vessel, HVH : Heating Ventilating Handling Unit)	Temporary	RPV Bellows Air 1/5Ch D/W HVH return 1/5Ch
CAMS radiation monitor	Data from temporary instrument. (CAMS : Containment Atmospheric Monitoring System)	Temporary	D/W System A 1/1Ch System B 1/1Ch S/C System A 1/1Ch System B 1/1Ch
Temperature in S/C	Data from temporary instrument, One representing value is noted among multiple data on each System A, B.	Temporary	System A1/4Ch (Unit 1), 8Ch (Unit 2/3) System B1/4Ch (Unit 1), 8Ch (Unit 2/3)
Hydrogen concentration in PCV	Data measured by the PCV gas management system. (PCV : Primary Containment Vessel)	Temporary	System 1/1
Temperature in the spent fuel pool	Data from temporary instrument. (Non-thermal mode : Urgent Heat load Mode、SHC mode : Shut down Cooling Mode)	Temporary	1/1Ch (Unit 2) 1/1 system (Unit 1/3/4)
FPC skimmer surge tank level	Unit2, 4 are the FPC skimmer surge tank level measured temporary instrument. Unit1, 3 are the FPC skimmer surge tank level estimated from temporary pressure gages,(reference value) (FPC: Fuel Pool Cooling system)	Temporary	1/1system

■Supplemental explanation for notes

ltem	Contents	Status As of 12:00 on February 26
Instrument failure	Instrument failure : down of instrument reading (over) scale/failure of instrument	Unit 1 CAMS D/W radiation monitor Unit 2 Pressure in S/C,RPV bellow air temperature, CAMS D/W(B) radiation monitor, CAMS S/C(B) radiation monitor Unit 3 —
	Unit4: Monitoring is not implemented since all fuel are takeoff. Unit5/6: Monitoring is not implemented since heat removal of reactor is functioning	
Continuously monitoring the status	Inaccurate Data defined from relation with other Parameters such as negative figure.	Unit 1 Reactor water level(B), Pressure in S/C Unit 2 Reactor water level(PM) return temperature Unit 3 Reactor water level, reactor pressure, RPV bellow air temperature, CAMS D/W(A) radiation monitor Unit1-2 Hydrogen Density of PCV: In case that the instrument indicates minus hydrogen density, "0%" is recorded. (Because there's the possibility of minus indication due to the instrumental precision when hydrogen density is very low.)