Fukushima Daiichi Nuclear Power Station Plant Parameters

As of 11:00 on April 14 2019

[Note]

Some indicators might not be functioning properly beyond the normal condition for usage affected by the earthquake and subsequent events. We comprehensively evaluate situation in plants using all the available information from indicators and also focusing on trends, taking uncertainty of indicators into consideration.

Status of water injection to the reactor FDW line : 2.4 m³/h #5 FDW line : 0.0 m³/h #5 FDW line : 1.5 m²/h CS line : 1.4 m³/h CS line : 2.4 m³/h CS line : 2.4 m³/h CS line : 2.4 m³/h (as of 11:00, 4/14)			
reactor $(as of 11:00 A/1A)$ $(as of 11:00 A/1A)$			
[las of 11:00, 4/14]			
VESSEL BOTTOM HEAD			
(TE-263-69L1): 14.7 °C VESSEL WALL ABOVE BOTTOM HEAD VESSEL BOTTOM ABOVE SKIRT JOT			
Temperature at VESSEL ABOVE SKIRT JOINT (TE-2-3-69H3): 21.0 ℃ (TE-2-3-69F1): 17.5 ℃			
the bottom of (TE-263-69H1): 14.6 °C RPV TEMPERATURE VESSEL WALL ABOVE BOTTOM HEAD			
RPV VESSEL DOWN COMMER (TE-2-3-69R): 20.8 ℃ (TE-2-3-69H1): 16.5 ℃			
(TE-263-69G2): 14.5 °C (as of 11:00, 4/14) (as of 11:00, 4/14)			
(as of 11:00, 4/14)			
HVH-12A RETURN AIR RETURN AIR DRYWELL COOLER RETURN AIR DRYWELL COOLER			
Temperature in (TE-1625A): 14.8 °C (TE-16-114B): 21.3 °C (TE-16-114A): 17.5 °C			
PCV HVH-12A SUPPLY AIR SUPPLY AIR D/W COOLER HVH2-16B SUPPLY AIR D/W COOLER			
(TE-1625F) : 14.4 ℃ (TE-16-114G#1) : 21.0 ℃ (TE-16-114F#1) : 16.3 ℃			
(as of 11:00, 4/14) (as of 11:00, 4/14)		_	
Pressure in PCV 0.06 kPa g 0.35 kPa g 0.35 kPa g			
(as of 11.00, 4/14) (as of 11.00, 4/14) (as of 11.00, 4/14)			
RPV (RVH): 13.96 Nm²/h			
Flow rate of (JP-A): 14.89 Nm²/h RPV: 10.42 Nm²/h RPV: 17.20 Nm²/h			
injection to GP-B) - Nm/n PCV - Nm/n	% 4		
Reactors **3 PCV: - Nm²/h			
(as of 11:00, 4/14)		4	
Outlet flow from PCV gas control 26.6 m³/h 12.48 Nm³/h 16.99 Nm³/h			
system (as of 11:00, 4/14) (as of 11:00, 4/14)			
Hydrogen System A: 0.00 vol% System A: 0.08 vol% System A: 0.07 vol%			
concentration in System B: 0.00 vol% System B: 0.07 vol% System B: 0.06 vol%			
PCV **1 (as of 11:00, 4/14) (as of 11:00, 4/14)			
System A: System A: System A:			
indicated value 1.03E-03 Bq/cm ³ indicated value ND Bq/cm ³ indicated value ND Bq/cm ³ detection limit 3.70E-04 Bq/cm ³			
Radioactive detection limit 3.70E-04 detection limit 1.5E-01 detection limit 2.2E-01			
concentration in PCV (Xe 135) System B: detection limit 3,70E-04 detection limit 1,5E-01 System B: System B: System B:			
$\frac{1}{2}$ indicated value 1.18E-03 $\frac{1}{800}$ indicated value ND $\frac{1}{800}$ indicated value ND $\frac{1}{800}$			
(as of 11:00, 4/14) (as of 11:00, 4/14)			
Temperature in the appart final 18.0 °C 16.7 °C		- ℃	% 6
the spent fuel pool (as of 11:00, 4/14) (as of 11:00, 4/14)		(as of 11:00, 4/14)	
FPC skimmer 4.17 m 3.11 m 3.11 m		67.4 ×100mm	
surge tank level (as of 11:00, 4/14) (as of 11:00, 4/14)		(as of 11:00, 4/14)	

[Information about measurements]

^{*1 :} In case that the instrument indicates minus hydrogen density, "0%" is recorded, (Because there's the possibility of minus indication due to the instrumental precision when hydrogen density is very low.)
The hydrogen concentration in the PCV gas control system is provided.

^{302:} In case that the instrument reading is below measurable limit, "ND" is recorded. The radioactivity density (Xe135) in the PCV gas control system is provided.

^{**3 :} Flow rate values are adjusted according to the temperature and the pressure under usage conditions.

^{※4 :} Nitrogen gas injection is under suspension.

^{*5:} The reactor injection water flow rate is changed due to work in progress.

^{※6:} The primary coolant pump in the Unit 4 spent fuel pool is now suspended.