Fukushima Daiichi Nuclear Power Station Plant Parameters

As of 11:00 on July 22 2019

[Note]

Some indicators might not be functioning properly beyond the normal condition for usage affected by the earthquake and subsequent events. We comprehensively evaluate situation in plants using all the available information from indicators and also focusing on trends, taking uncertainty of indicators into consideration.

	Unit 1	Unit 2	Unit 3	Unit 4
	FDW line : 1.5 m²/h CS line : 1.4 m²/h	FDW line: 1.4 m³/h CS line: 1.5 m³/h	FDW line : 1.5 m ¹ /h CS line : 1.5 m ¹ /h	
	(as of 11:00, 7/22)	(as of 11:00, 7/22)	(as of 11:00, 7/22)	
	VESSEL BOTTOM HEAD	(as 01 11.00; 7/22)	(as of 11.00, 1/22)	
Temperature at the bottom of RPV	(TE-263-69L1) : 23.7 °C VESSEL ABOVE SKIRT JOINT (TE-263-69H1) : 23.6 °C	VESSEL WALL ABOVE BOTTOM HEAD (TE-2-3-69H3): 28.9 °C RPV TEMPERATURE	VESSEL BOTTOM ABOVE SKIRT JOT (TE-2-3-69F1) : 27.0 °C VESSEL WALL ABOVE BOTTOM HEAD	
	(TE-263-6961) 23.0 C VESSEL DOWN COMMER (TE-263-6962) : 23.5 °C (as of 11:00, 7/22)	(TE-2-3-69R) : 30.1 °C (as of 11:00, 7/22)	(TE-2-3-69H1) : 26.0 °C (as of 11:00, 7/22)	
Temperature in PCV	HVH-12A RETURN AIR (TE-1625A): 23.8 °C	RETURN AIR DRYWELL COOLER (TE-16-114B) : 29.8 °C	RETURN AIR DRYWELL COOLER (TE-16-114A) : 27.3 °C	
	HVH-12A SUPPLY AIR (TE-1625F): 23.6 °C (as of 11:00, 7/22)	SUPPLY AIR D/W COOLER HVH2-16B (TE-16-114G#1) : 29.2 °C (as of 11:00, 7/22.)	SUPPLY AIR D/W COOLER (TE-16-114F#1) : 25.6 °C (as of 11:00, 7/22)	_
Pressure in PCV	0.40 kPa g (as of 11:00 , 7/22)	3.04 kPa g (as of 11:00, 7/22)	0.40 kPag (as of 11:00, 7/22)	
Flow rate of nitrogen gas injection to Reactors %3	RPV (RVH) : - Nm³/h %6 (JP-A) : 27.99 Nm³/h %6 (JP-B) : - Nm³/h %6 PCV : - Nm³/h %4	RPV: 8.21 Nm ² /h PCV: - Nm ² /h	RPV : 16.94 Nm³/h PCV : - Nm³/h	
Outlet flow from PCV gas control		14.97 Nm²/h (as of 11:00 , 7/22)	17.98 Nm ² /h (as of 11:00 , 7/22)	
system Hydrogen concentration in PCV %1	System A : 0.00 vol%	System A : 0.08 vol% System B : 0.08 vol% (as of 11:00 , 7/22)	System A : 0.06 vol% System B : 0.06 vol% (as of 11:00, 7/22.)	
Radioactive concentration in PCV (Xe 135) ※2 Temperature in	indicated value 1.23E-03	System A : indicated value ND Bq/cm ² detection limit 1.5E-O1 Bq/cm ² System B : indicated value ND Bq/cm ² detection limit 1.4E-O1	System A : indicated value ND Bq/cm ² detection limit 2.2E-01 Bq/cm ² System B : indicated value ND Bq/cm ² detection limit 2.2E-01 Bq/cm ²	
	(as of 11:00 , 7/22)	(as of 11:00 , 7/22)	(as of 11:00 , 7/22)	°2
the spent fuel	29.9 °C	30.3 °C	29.6 °C	- °C **5
	(as of 11:00, 7/22) 3.33 m (as of 11:00, 7/22)	(as of 11:00, 7/22) 3.61 m (as of 11:00, 7/22)	(as of 11:00, 7/22) 2.56 m (as of 11:00, 7/22)	(as of 11:00 , 7/22) 67.1 ×100mm (as of 11:00 , 7/22)

[Information about measurements]

*1: In case that the instrument indicates minus hydrogen density, "0%" is recorded. (Because there's the possibility of minus indication due to the instrumental precision when hydrogen density is very low.)

The hydrogen concentration in the PCV gas control system is provided.

*2 : In case that the instrument reading is below measurable limit, "ND" is recorded. The radioactivity density (Xe135) in the PCV gas control system is provided.

*3 : Flow rate values are adjusted according to the temperature and the pressure under usage conditions.

%4 : Nitrogen gas injection is under suspension.

*5 : The primary coolant pump in the Unit 4 spent fuel pool is now suspended.

%6 : Change of the nitrogen injection amount (PTW)

*7 : Data missing due to work interrupting the measurement.